

Modelo	Monofásico (1φ)	Estándar	PUHZ-SHW80VAA	PUHZ-SHW112VAA	--	--
		Protección salina	PUHZ-SHW80VAA-BS	PUHZ-SHW112VAA-BS	--	--
	Trifásico (3φ)	Estándar	PUHZ-SHW80YAA	PUHZ-SHW112YAA	PUHZ-SHW140YHA	PUHZ-SHW230YKA
		Protección salina	PUHZ-SHW80YAA-BS	PUHZ-SHW112YAA-BS	PUHZ-SHW140YHA-BS	--

Especificaciones unidades exteriores

Capacidad nominal			7°C			2°C			-7°C			7°C			2°C			-7°C		
			7°C	2°C	-7°C	7°C	2°C	-7°C	7°C	2°C	-7°C	7°C	2°C	-7°C	7°C	2°C	-7°C			
Capacidad nominal	Calefacción	Temperatura exterior	7°C	2°C	-7°C	7°C	2°C	-7°C	7°C	2°C	-7°C	7°C	2°C	-7°C	7°C	2°C	-7°C			
		Capacidad	kW	8,00	8,00	8,00	11,20	11,20	11,20	14,00	14,00	14,00	23,00	23,00	23,00	23,00	23,00	23,00		
		Agua: 35°C	COP	4,65	3,55	3,48	4,46	3,22	3,34	4,22	2,96	2,58	3,65	2,37	2,85	3,65	2,37	2,85		
		Consumo	kW	1,72	2,25	2,30	2,51	3,48	3,35	3,32	4,73	5,43	6,30	9,70	8,07	6,30	9,70	8,07		
		Capacidad	kW	8,00	7,69	8,00	11,20	10,37	10,76	14,00	14,00	14,00	23,00	22,78	23,00	23,00	22,78	23,00		
		Agua: 55°C	COP	2,70	2,15	2,02	2,71	1,94	1,95	2,49	1,89	1,64	2,47	2,02	2,11	2,47	2,02	2,11		
	Consumo	kW	2,96	3,58	3,96	4,13	5,35	5,52	5,62	7,41	8,54	9,31	11,28	10,90	9,31	11,28	10,90			
	Refrigeración	Temperatura agua		7°C	18°C	7°C	18°C	7°C	18°C	7°C	18°C	7°C	18°C	7°C	18°C	7°C	18°C			
		Capacidad	kW	7,10	7,10	10,00	10,00	10,00	10,00	12,50	12,50	20,00	20,00	20,00	20,00	20,00	20,00			
Aire: 35°C		EER	3,31	4,52	2,83	4,74	2,17	4,26	2,17	4,26	2,22	3,55	2,22	3,55	2,22	3,55				
	Consumo	kW	2,15	1,57	3,53	2,11	5,76	2,93	9,01	5,63	9,01	5,63	9,01	5,63	9,01	5,63				
Datos eléctricos	Alimentación (V, Hz)		1φ: 230, 50		3φ: 400, 50		1φ: 230, 50		3φ: 400, 50		400, 50		400, 50		400, 50					
	Corriente máx.	A	1φ: 22,0		3φ: 13,0		1φ: 28		3φ: 13,0		13,0		26,0		26,0					
	Tamaño PIA	A	1φ: 25		3φ: 16		1φ: 32		3φ: 16		16		32		32					
Dimensiones	Al. x An. x Fo.	mm	1020 x 1050 x 480				1020 x 1050 x 480				1350 x 950 x 330				1338 x 1050 x 330					
	Peso	kg	1φ: 116		3φ: 128		1φ: 116		3φ: 128		134		149		149		149			
Tuberías frigoríficas	Ø Líquido / Gas		9,52mm (3/8") / 15,88mm (5/8")				9,52mm (3/8") / 15,88mm (5/8")				9,52mm (3/8") / 15,88mm (5/8")				12,7mm (1/2") / 25,4mm (1")					
	L.máx./Altura máx.	m	75 / 30				75 / 30				75 / 30				80 / 30					
Sonido	SPL / PWL	dB(A)	45 / 59				47 / 60				52 / 70				59 / 75					
	Tipo		Hermetic scroll				Hermetic scroll				Hermetic scroll				Hermetic scroll					
Compresor	Modelo		1φ:DNK28FBAMT		3φ:DNK28FBBMT		1φ:DNK28FBAMT		3φ:DNK28FBBMT		ANB33FJOMT		ANB66FJNMT		ANB33FJOMT		ANB66FJNMT			
	Calor	°C	-28 — +24				-28 — +24				-28 — +24				-25 — +21					
Rango operativo	ACS	°C	-28 — +35				-28 — +35				-28 — +35				-25 — +35					
	Frío	°C	+10 — +46				+10 — +46				+10 — +46				+10 — +46					