

Ficha técnica

Modelo	Monofásico 1φ	Estándar	PUHZ-SW100VAA	PUHZ-SW120VHA	--	--
		Protección salina	PUHZ-SW100VAA-BS	PUHZ-SW120VHA-BS	--	--
	Trifásico 3φ	Estándar	PUHZ-SW100YAA	PUHZ-SW120YHA	PUHZ-SW160YKA	PUHZ-SW200YKA
		Protección salina	PUHZ-SW100YAA-BS	PUHZ-SW120YHA-BS	PUHZ-SW160YKA-BS	PUHZ-SW200YKA-BS

Especificaciones unidades exteriores

Capacidad nominal		Temperatura exterior	7°C	2°C	-7°C	7°C	2°C	-7°C	7°C	2°C	-7°C	7°C	2°C	-7°C			
			7°C	18°C	7°C	18°C	7°C	18°C	7°C	18°C	7°C	18°C					
Capacidad nominal	Calefacción	Capacidad	11,20	10,00	8,90	16,00	12,00	11,20	22,00	16,00	13,42	25,00	20,00	15,32			
		Agua: COP	4,46	3,32	3,20	4,10	3,24	2,85	4,20	3,11	2,80	4,00	2,80	2,67			
		Consumo	2,51	3,01	2,78	3,90	3,70	3,93	5,24	5,14	4,79	6,25	7,14	5,74			
	Refrigeración	Capacidad	11,20	10,00	8,90	15,21	12,00	11,20	22,00	16,00	11,79	25,00	20,00	13,60			
		Agua: COP	2,71	2,13	1,79	2,52	1,86	1,68	2,47	1,87	1,76	2,45	1,73	1,69			
		Consumo	4,13	4,69	4,97	6,04	6,45	6,67	8,91	8,56	6,70	10,20	11,56	8,05			
Datos eléctricos	Temperatura agua	7°C	18°C	7°C	18°C	7°C	18°C	7°C	18°C	7°C	18°C	7°C	18°C				
	Capacidad	10,00	10,00	12,50	14,00	16,00	18,00	20,00	22,00	2,83	4,74	2,25	4,10				
	Aire: EER	2,83	4,74	2,32	4,08	2,76	4,56	2,25	4,10	3,53	2,11	5,39	3,43				
Dimensiones	Consumo	3,53	2,11	5,39	3,43	5,80	3,95	8,89	5,37	1φ: 230, 50	3φ: 400, 50	1φ: 230, 50	3φ: 400, 50				
	Alimentación (V, Hz)	1φ: 230, 50	3φ: 400, 50	1φ: 230, 50	3φ: 400, 50	400, 50		400, 50		1φ: 28,0	3φ: 13,0	1φ: 29,5	3φ: 13,0				
	Corriente máx.	1φ: 28,0	3φ: 13,0	1φ: 29,5	3φ: 13,0	19,0		21,0		1φ: 32	3φ: 16	1φ: 32	3φ: 16				
Tuberías frigoríficas	Tamaño PIA	1φ: 32	3φ: 16	1φ: 32	3φ: 16	25		32		1020 x 1050 x 480							
	Al. x An. x Fo.	1020 x 1050 x 480				1350 x 950 x 330				1338 x 1050 x 330							
	Peso	1φ: 114				3φ: 126				1φ: 118				3φ: 130			
Sonido	Ø Líquido / Gas	9,52mm (3/8") / 15,88mm (5/8")				9,52mm (3/8") / 15,88mm (5/8")				9,52mm (3/8") / 25,4mm (1")				12,7mm (1/2") / 25,4mm (1")			
	L.máx./Altura máx.	75 / 30				75 / 30				80 / 30				80 / 30			
Compresor	SPL / PWL	47 / 60				54 / 72				62 / 78				62 / 78			
	Tipo	Hermetic				Hermetic scroll				Hermetic scroll				Hermetic scroll			
Rango operativo	Modelo	1φ: DNB28FBAMT 3φ: DNB28FB8MT				1φ: ANB42FNEMT 3φ: ANB42FN8MT				ANB52FRNMT				ANB52FRNMT			
	Calor	-20 — +24				-20 — +21				-20 — +21				-20 — +21			
	ACS	-20 — +35				-20 — +35				-20 — +35				-20 — +35			
	Frio	+10 — +46				+10 — +46				+10 — +46				+10 — +46			