

UNIDAD EXTERIOR			HU121MA.U33	HU141MA.U33	HU161MA.U33	HU123MA.U33	HU143MA.U33	HU163MA.U33
Rango de operación	Frío (°DB)	Mín. - Máx.	5 ~ 48	5 ~ 48	5 ~ 48	5 ~ 48	5 ~ 48	5 ~ 48
	Calor (°WB)	Mín. - Máx.	-25 ~ 35	-25 ~ 35	-25 ~ 35	-25 ~ 35	-25 ~ 35	-25 ~ 35
Potencia sonora Calor (dBA)			63	64	65	63	64	65
Caudal de aire (m <sup>3</sup> /min.)			55x2	55x2	55x2	55x2	55x2	55x2
Dimensiones (An. x AL x Prof) (mm)			950x1.380x330	950x1.380x330	950x1.380x330	950x1.380x330	950x1.380x330	950x1.380x330
Peso (kg)			84,8	84,8	84,8	85,4	85,4	85,4
Conexiones	Circuito de agua	Entrada (mm/in)	PT 25, macho	PT 25, macho	PT 25, macho	PT 25, macho	PT 25, macho	PT 25, macho
		Salida (mm/in)	PT 25, macho	PT 25, macho	PT 25, macho	PT 25, macho	PT 25, macho	PT 25, macho
	Circuito refrigerante	Líquido (mm/in)	Ø 9,52 (3/8)	Ø 9,52 (3/8)	Ø 9,52 (3/8)	Ø 9,52 (3/8)	Ø 9,52 (3/8)	Ø 9,52 (3/8)
		Gas (mm/in)	Ø 15,88 (5/8)	Ø 15,88 (5/8)	Ø 15,88 (5/8)	Ø 15,88 (5/8)	Ø 15,88 (5/8)	Ø 15,88 (5/8)
Refrigerante (R410A)	Precarga para 7,5m (kg)		2,5	2,5	2,5	2,5	2,5	2,5
	Longitud tubería precarga (ml)		7,5	7,5	7,5	7,5	7,5	7,5
	t-CO <sub>2</sub> eq.		5,22	5,22	5,22	5,22	5,22	5,22
	Refrigerante adicional (g/m)		40	40	40	40	40	40
Longitudes	Máxima (m)		50	50	50	50	50	50
	Desnivel (m)		30	30	30	30	30	30
			3.733 €	4.610 €	5.500 €	3.970 €	4.871 €	5.876 €