

# CONFORT +

## Cassette (monofásico)

CONJUNTO	9	12	18	24	30	36	42	48	60	
Capacidad	Frío (kW) Min-Nom-Máx	1.50-2.50-3.20	1.50-3.40-4.50	2.00-5.00-5.80	2.70-6.80-8.00	3.20-8.00-9.20	3.80-9.50-12.54	4.80-12.10-14.16	5.40-13.40-15.68	5.80-14.60-15.77
	Calor (kW) Min-Nom-Máx	1.80-3.20-3.70	1.80-4.10-5.00	2.30-5.70-6.60	3.00-7.50-9.00	3.60-8.90-10.10	4.30-10.80-13.39	5.40-13.50-15.80	6.20-15.50-17.52	6.80-16.90-18.25
Consumo nominal	Frío (kW) Min-Nom-Máx	0.30-0.61-0.87	0.30-0.97-1.62	0.30-1.57-2.20	0.40-1.93-2.66	0.50-2.45-3.44	0.50-2.26-3.44	0.70-3.31-4.30	0.90-4.25-5.53	1.00-5.21-5.84
	Calor (kW) Min-Nom-Máx	0.30-0.75-0.89	0.30-1.11-1.57	0.30-1.52-2.13	0.40-1.96-2.84	0.50-2.62-3.25	0.50-2.43-3.30	0.70-3.51-4.56	0.90-4.37-5.33	1.00-5.12-5.89
E.E.R		4,10	3,51	3,19	3,52	3,27	4,20	3,66	3,15	2,80
S.E.E.R		6,70	6,70	6,40	7,40	7,10	4,00	4,00	6,50	6,20
C.O.P		4,30	3,71	3,74	3,83	3,40	4,45	3,85	3,55	3,30
S.C.O.P		4,00	4,00	4,30	4,30	4,30	4,30	4,30	4,20	4,20
Etiqueta energética (A+++ a D)		A++/A+	A++/A+	A++/A+	A++/A+	A++/A+	A++/A+	-	-	-
<b>PVP 2022</b>										

**Nota:** el precio del conjunto incluye: unidad exterior + unidad interior + panel + mando PREMTB001.

UNIDAD INTERIOR	CT09F.NR0	CT12F.NR0	CT18F.NQ0	CT24F.NB0	UT30F.NB0	UT36F.NA0	UT42F.NA0	UT48F.NA0	UT60F.NA0
Presión sonora	36 / 33 / 30	38 / 35 / 32	41 / 39 / 37	38 / 36 / 34	40 / 37 / 35	44 / 42 / 41	44 / 42 / 41	46 / 44 / 42	46 / 44 / 42
Caudal de aire (H/M/L)(m³/min)	8.5 / 7 / 6	9.5 / 8 / 7	13 / 12 / 11	17/15/13	19/17/15.5	27.5 / 25 / 22.5	27.5 / 25 / 22.5	30/27.5/25	30/27.5/25
Dimensiones (An. x Al. x Prof.) (mm)	570x214x570	570x214x570	570x256x570	840x204x840	840x204x840	840x288x840	840x288x840	840x288x840	840x288x840
Peso IDU (kg)	12,4	12,4	13,9	21,1	21,1	25,3	25,3	25,3	25,3
Panel	PT-QAGW0	PT-QAGW0	PT-QAGW0	PT-AAGW0* Dual Vane	PT-AAGW0* Dual Vane	PT-AAGW0* Dual Vane	PT-AAGW0* Dual Vane	PT-AAGW0* Dual Vane	PT-AAGW0* Dual Vane
Dimensiones (An x Al x Prof.) (mm)	620x35 620	620x35x620	620x35x620	950x35x950	950x35x950	950x35x950	950x35x950	950 x 35 x 950	950 x 35 x 950
Panel (kg)	3	3	3	7,1	7,1	7,1	7,1	7,1	7,1
Conexiones frigoríficas	Líquido (mm / pulgada)	Ø 6.35 (1/4)	Ø 6.35 (1/4)	Ø 6.35 (1/4)	Ø 9.52 (3/8)	Ø 9.52 (3/8)	Ø 9.52 (3/8)	Ø 9.52 (3/8)	Ø 9.52 (3/8)
	Gas (mm / pulgada)	Ø 9.52 (3/8)	Ø 9.52 (3/8)	Ø 12.7 (1/2)	Ø 15.88 (5/8)	Ø 15.88 (5/8)	Ø 15.88 (5/8)	Ø 15.88 (5/8)	Ø 15.88 (5/8)

\*Opcional el panel PT-AFGW0. (Ver tabla de accesorios).

UNIDAD EXTERIOR	UUA1.U10	UUB1.U20	UUC1.U40	UUD1.U30						
Presión sonora	Frío (dB(A))	49	49	47	48	50	50	51	52	54
	Calor (dB(A))	52	52	52	52	52	50	52	53	54
Caudal de aire (m³/min)	28 x 1		50 x 1	58 x 1		55 x 2				
Dimensiones (An. x Al. x Prof.) (mm)	770 x 545 x 288		870 x 650 x 330	950 x 834 x 330		950 x 1.380 x 330				
Peso (kg)	33,3		44,5	59		89				
Refrigerante (R32)	Precarga (kg)	1		1,2		1,9		3		
	Longitud tubería precarga (ml)	7,5		7,5		7,5		7,5		
	T- CO <sub>2</sub> eq	0,68		0,81		1,28		2,21		
	Refrigerante adicional (g/m)	20		20		40		40		
Rango de operación	Frío (Máx / Mín) (°C CB)	50 / -15		50 / -15		50 / -20		52 / -20		
	Calor (Máx / Mín) (°C WB)	18 / -20		18 / -20		18 / -20		18 / -25		
Conexiones frigoríficas	Líquido (mm / pulgada)	Ø 6.35 (1/4)		Ø 6.35 (1/4)		Ø 9.52 (3/8)		Ø 9.52 (3/8)		
	Gas (mm / pulgada)	Ø 9.52 (3/8)		Ø 12.7 (1/2)		Ø 15.88 (5/8)		Ø 15.88 (5/8)		
Longitudes	Total, mín / máx (m)	5 / 30		5 / 30		5 / 50		5 / 85		
	Desnivel (m)	20		20		40		40		

UNIDAD INTERIOR									
UNIDAD EXTERIOR									
PANEL									
MANDO									