

Model		Indoor	CS-Z25ZKEW, CS-XZ25ZKEW, CS-XZ25ZKEW-H			
		Outdoor	CU-Z25ZKE			
Performance Test Condition		EUROVENT				
Power Supply		Phase, Hz	Single, 50			
		V	230			
			Min.	Mid.	Max	
Cooling	Capacity	kW	0.85	2.50	3.50	
		BTU/h	2900	8530	11900	
		kcal/h	730	2150	3010	
	Running Current	A	-	2.40	-	
	Input Power	W	170	510	900	
	Annual Consumption	kWh	-	255	-	
	EER Class		-	A	-	
	EER	W/W	5.00	4.90	3.89	
		BTU/hW	17.06	16.73	13.22	
		kcal/hW	4.29	4.22	3.34	
	ErP	Pdesign	kW	2.5		
		SEER	(W/W)	9.5		
		Annual Consumption	kWh	92		
		Class		A+++		
	Power Factor	%	-	92	-	
	Indoor Noise (H / L / QLo)	dB (A)	39 / 25 / 19			
		Power Level dB (A)	55 / - / -			
	Outdoor Noise (H / L / QLo)	dB (A)	46 / - / -			
Power Level dB (A)		61 / - / -				
Heating	Capacity	kW	0.80	3.40	4.80	
		BTU/h	2730	11600	16400	
		kcal/h	690	2920	4130	
	Running Current	A	-	3.20	-	
	Input Power	W	160	700	1.18k	
	COP CLASS		-	A	-	
	COP	W/W	5.00	4.86	4.07	
		BTU/hW	17.06	16.57	13.90	
		kcal/hW	4.31	4.17	3.50	
	ErP	Pdesign	kW	2.6		
		Tbivalent	°C	-10		
		SCOP	(W/W)	5.2		
		Annual Consumption	kWh	700		
		Class		A+++		
	Warmer Zone					
	ErP	Pdesign	kW	1.5		
		Tbivalent	°C	2		
		TOL	°C	-20		
SCOP		(W/W)	6.2			
Annual Consumption		kWh	339			
Class			A+++			
Power Factor	%	-	95	-		
Indoor Noise (H / L / QLo)	dB (A)	39 / 27 / 19				
	Power Level dB (A)	55 / - / -				
Outdoor Noise (H / L / QLo)	dB (A)	47 / - / -				
	Power Level dB (A)	62 / - / -				
LOW Temp: Capacity (kW) / I. Power W) / COP			3.48 / 1.04k / 3.35			
EXTR LOW Temp: Capacity (kW) / I. Power W) / COP			2.80 / 1.00k / 2.80			
Max Current (A) / Max Input Power (W)			5.3 / 1.18k			
Starting Current (A)			3.20			