

Model		Indoor	CS-TZ50ZKEW			CS-TZ60ZKEW			
		Outdoor	CU-TZ50ZKE			CU-TZ60ZKE			
Performance Test Condition			EUROVENT			EUROVENT			
Power Supply		Phase, Hz	Single, 50			Single, 50			
		V	230			230			
			Min.	Mid.	Max.	Min.	Mid.	Max.	
Cooling	Capacity		kW	0.98	5.00	5.60	0.98	6.00	6.60
			BTU/h	3340	17100	19100	3340	20500	22500
			kcal/h	840	4300	4820	840	5160	5680
	Running Current		A	–	7.00	–	–	8.10	–
	Input Power		W	250	1.60k	1.89k	250	1.85k	2.30k
	Annual Consumption		kWh	–	800	–	–	925	–
	EER		W/W	3.92	3.13	2.96	3.92	3.24	2.87
			BTU/hW	13.36	10.69	10.11	13.36	11.08	9.78
			kcal/hW	3.36	2.69	2.55	3.36	2.79	2.47
	ErP		Pdesign	kW			6.0		
			SEER	(W/W)			6.8		
			Annual Consumption	kWh			309		
			Class				A++		
	Power Factor		%	–	99	–	–	99	–
	Indoor Noise (H / L / QLo)		Pressure Level (dB(A))	44 / 37 / 33			45 / 37 / 34		
			Power Level dB	60 / – / –			60 / – / –		
	Outdoor Noise (H / L)		Pressure Level (dB(A))	48 / –			49 / –		
			Power Level dB	63 / –			64 / –		
Heating	Capacity		kW	0.98	5.80	7.50	0.98	7.00	8.20
			BTU/h	3340	19800	25600	3340	23900	28000
			kcal/h	840	4990	6450	840	6020	7050
	Running Current		A	–	7.60	–	–	8.30	–
	Input Power		W	210	1.70k	2.30k	210	1.88k	2.30k
	COP		W/W	4.67	3.41	3.26	4.67	3.72	3.57
			BTU/hW	15.90	11.65	11.13	15.90	12.71	12.17
			kcal/hW	4.00	2.94	2.80	4.00	3.20	3.07
	ErP		Pdesign	kW			4.4		
			Tbivalent	°C			-10		
			SCOP	(W/W)			4.3		
			Annual Consumption	kWh			1433		
			Class				A+		
	Power Factor		%	–	97	–	–	98	–
	Indoor Noise (H / L / QLo)		Pressure Level (dB(A))	44 / 37 / 33			45 / 37 / 34		
			Power Level dB	60 / – / –			61 / – / –		
	Outdoor Noise (H / L)		Pressure Level (dB(A))	49 / –			51 / –		
			Power Level dB	64 / –			66 / –		
Low Temp. : Capacity (kW) / I.Power (W) / COP			5.43 / 2.04k / 2.66			5.94 / 2.04k / 2.91			
Extr Low Temp. : Capacity (kW) / I.Power (W) / COP			4.62 / 2.00k / 2.31			4.90 / 1.87k / 2.62			
Max Current (A) / Max Input Power (W)			10.5 / 2.30k			11.2 / 2.50k			
Starting Current (A)			7.60			8.30			