

Model		Indoor	CS-Z35ZKEW, CS-XZ35ZKEW, CS-XZ35ZKEW-H			
		Outdoor	CU-Z35ZKE			
Performance Test Condition		EUROVENT				
Power Supply		Phase, Hz	Single, 50			
		V	230			
			Min.	Mid.	Max	
Cooling	Capacity	kW	0.85	3.50	4.20	
		BTU/h	2900	11900	14300	
		kcal/h	730	3010	3610	
	Running Current	A	-	3.70	-	
	Input Power	W	200	820	1.16k	
	Annual Consumption	kWh	-	410	-	
	EER CLASS		-	A	-	
	EER	W/W	4.25	4.27	3.62	
		BTU/hW	14.5	14.51	12.33	
		kcal/hW	3.65	3.67	3.11	
	ErP	Pdesign	kW	3.5		
		SEER	(W/W)	9.5		
		Annual Consumption	kWh	129		
		Class		A+++		
	Power Factor	%	-	96	-	
	Indoor Noise (H / L / QLo)	dB (A)	42 / 28 / 19			
		Power Level dB (A)	58 / - / -			
Outdoor Noise (H / L / QLo)	dB (A)	48 / - / -				
	Power Level dB (A)	63 / - / -				
Heating	Capacity	kW	0.80	4.00	5.50	
		BTU/h	2730	13600	18800	
		kcal/h	690	3440	4730	
	Running Current	A	-	4.00	-	
	Input Power	W	180	880	1.46k	
	COP CLASS		-	A	-	
	COP	W/W	4.44	4.55	3.77	
		BTU/hW	15.17	15.45	12.88	
		kcal/hW	3.83	3.91	3.24	
	ErP	Pdesign	kW	2.9		
		Tbivalent	°C	-10		
		SCOP	(W/W)	5.2		
		Annual Consumption	kWh	781		
		Class		A+++		
	Warmer Zone					
	ErP	Pdesign	kW	1.6		
		Tbivalent	°C	2		
TOL		°C	-20			
SCOP		(W/W)	6.2			
Annual Consumption		kWh	361			
Class			A+++			
Power Factor	%	-	96	-		
Indoor Noise (H / L / QLo)	dB (A)	43 / 33 / 19				
	Power Level dB (A)	59 / - / -				
Outdoor Noise (H / L / QLo)	dB (A)	50 / - / -				
	Power Level dB (A)	65 / - / -				
LOW Temp: Capacity (kW) / I. Power W) / COP		3.99 / 1.29k / 3.09				
EXTR LOW Temp: Capacity (kW) / I. Power W) / COP		3.20 / 1.26k / 2.54				
Max Current (A) / Max Input Power (W)		6.4 / 1.46k				
Starting Current (A)		4.00				