

Model		Indoor	CS-Z42ZKEW, CS-XZ42ZKEW-H			
		Outdoor	CU-Z42ZKE			
Performance Test Condition		EUROVENT				
Power Supply		Phase, Hz	Single, 50			
		V	230			
			Min.	Mid.	Max	
Cooling	Capacity	kW	0.85	4.20	5.00	
		BTU/h	2900	14300	17100	
		kcal/h	730	3610	4300	
	Running Current	A	-	5.50	-	
	Input Power	W	235	1.24k	1.57k	
	Annual Consumption	kWh	-	620	-	
	EER CLASS		-	A	-	
	EER	W/W	3.62	3.39	3.18	
		BTU/hW	12.34	11.53	10.89	
		kcal/hW	3.11	2.91	2.74	
	ErP	Pdesign	kW	4.2		
		SEER	(W/W)	7.1		
		Annual Consumption	kWh	207		
		Class		A++		
	Power Factor	%	-	98	-	
	Indoor Noise (H / L / QLo)	dB (A)	43 / 31 / 25			
Power Level dB (A)		59 / - / -				
Outdoor Noise (H / L / QLo)	dB (A)	49 / - / -				
	Power Level dB (A)	64 / - / -				
Heating	Capacity	kW	0.80	5.30	6.80	
		BTU/h	2730	18100	23200	
		kcal/h	690	4560	5850	
	Running Current	A	-	6.30	-	
	Input Power	W	190	1.42k	1.86k	
	COP CLASS		-	A	-	
	COP	W/W	4.21	3.73	3.66	
		BTU/hW	14.37	12.75	12.47	
		kcal/hW	3.63	3.21	3.15	
	ErP	Pdesign	kW	3.6		
		Tbivalent	°C	-10		
		SCOP	(W/W)	4.3		
		Annual Consumption	kWh	1172		
		Class		A+		
	Warmer Zone					
	ErP	Pdesign	kW	1.9		
Tbivalent		°C	2			
TOL		°C	-20			
SCOP		(W/W)	5.8			
Annual Consumption		kWh	459			
Class			A+++			
Power Factor	%	-	98	-		
Indoor Noise (H / L / QLo)	dB (A)	43 / 35 / 29				
	Power Level dB (A)	59 / - / -				
Outdoor Noise (H / L / QLo)	dB (A)	51 / - / -				
	Power Level dB (A)	66 / - / -				
LOW Temp: Capacity (kW) / I. Power W) / COP			4.93 / 1.65k / 2.99			
EXTR LOW Temp: Capacity (kW) / I. Power W) / COP			4.11 / 1.52k / 2.70			
Max Current (A) / Max Input Power (W)			8.1 / 1.86k			
Starting Current (A)			6.30			