

Model		Indoor	CS-Z50ZKEW, CS-XZ50ZKEW			
		Outdoor	CU-Z50ZKE			
Performance Test Condition		EUROVENT				
Power Supply		Phase, Hz	Single, 50			
		V	230			
		Min.	Mid.	Max.		
Cooling	Capacity		kW	0.98	5.00	6.00
			BTU/h	3340	17100	20500
			kcal/h	840	4300	5160
	Running Current		A	–	6.00	–
	Input Power		W	250	1.36k	1.90k
	Annual Consumption		kWh	–	680	–
	EER		W/W	3.92	3.68	3.16
			BTU/hW	13.36	12.57	10.79
			kcal/hW	3.36	3.16	2.72
	ErP	Pdesign	kW	5.0		
		SEER	(W/W)	8.5		
		Annual Consumption	kWh	206		
		Class		A+++		
	Power Factor		%	–	99	–
	Indoor Noise (H / L / QLo)		dB-A	44 / 37 / 30		
			Power Level dB	60 / - / -		
	Outdoor Noise (H / L)		dB-A	47 / –		
Power Level dB			62 / –			
Heating	Capacity		kW	0.98	5.80	8.00
			BTU/h	3340	19800	27300
			kcal/h	840	4990	6880
	Running Current		A	–	6.20	–
	Input Power		W	230	1.40k	2.39k
	COP		W/W	4.26	4.14	3.35
			BTU/hW	14.52	14.14	11.42
			kcal/hW	3.65	3.56	2.88
	ErP	Pdesign	kW	4.2		
		Tbivalent	°C	-10		
		SCOP	(W/W)	4.8		
		Annual Consumption	kWh	1225		
		Class		A++		
	Warmer Zone					
	ErP	Pdesign	kW	2.3		
		Tbivalent	°C	2		
		TOL	°C	-20		
SCOP		(W/W)	6.0			
Annual Consumption		kWh	537			
Class			A+++			
Power Factor		%	–	98	–	
Indoor Noise (H / L / QLo)		dB-A	44 / 37 / 30			
		Power Level dB	60 / - / -			
Outdoor Noise (H / L)		dB-A	47 / –			
		Power Level dB	62 / –			
Low Temp. : Capacity (kW) / I.Power (W) / COP			5.80 / 2.12k / 2.74			
Extr Low Temp. : Capacity (kW) / I.Power (W) / COP			4.80 / 1.88k / 2.55			
Max Current (A) / Max Input Power (W)			10.5 / 2.39k			
Starting Current (A)			6.20			