

Conductos presión media Health-Connect



Presión estática regulable mediante el control por cable (máx. de 10 pasos)

Modelo	kW	E. Class (SEER/SCOP)	Mono R32	*Multi R32 (Compatibilidad)
AD35S2SM3FA(H)*/1U35S2SM1FA-2	3,5	A++/A	X	X
AD50S2SM3FA(H)*/1U50S2S2FA	5,0	A++/A	X	X
AD71S2SM3FA(H)*/1U71S2SR2FA	7,1	A++/A	X	X
**AD90S2SM3FA(H)/1U90S2S2FA	9,0	A++/A	X	
AD105S2SM3FA(H)/1U105S2S2FA	10,5	A++/A	X	
AD125S2SM3FA(H)/1U125S2SN2FA-B	12,5	A+/A	X	
AD140S2SM3FA(H)/1U140S2SN1FA-B AD140S2SM3FA(H)/1U140S2SP2FA-B	14,0	A+/A	X	
AD160S2SM3FA(H)/1U160S2SP1FB	16,0	A+/A+	X	



Silencioso



Diseño compacto



Aire fresco



Bomba de drenaje de condensación



Fácil instalación



Esterilización UVC



Control por Wi-Fi integrado

* Para los tamaños de 3,5 kW y 5,0 kW desde el 3U55S2SR5FA y superiores

Para el tamaño 7,1 kW desde el 3U70S2SR5FA y superiores

** Disponible a partir de Septiembre 2023