

MODELOS

		GIA-CF-18ADMR32	GIA-CF-24ADMR32	GIA-CF-36ADMR32	GIA-CF-42ADMR32	GIA-CFT3-48ADMR32	GIA-CFT3-60ADMR32
INT.		GIA-CFI-18ADMR32	GIA-CFI-24ADMR32	GIA-CFI-36ADMR32	GIA-CFI-42ADMR32	GIA-CFI-48ADMR32	GIA-CFI-60ADMR32
EXT.		GIA-U0-18ADMR32	GIA-U0-24ADMR32	GIA-U0-36ADMR32	GIA-U0-42ADMR32	GIA-UOT3-48ADMR32	GIA-UOT3-60ADMR32

Alimentación eléctrica / Conexión V,F,Hz 220-240V (1 Fase ~ 50Hz) Unidad exterior 380-415 (1 Fase ~ 50Hz) Unidad exterior

RENDIMIENTO

Capacidad refrigeración	Capacidad	kW	5.28 (2.71-5.86)	7.03 (3.22-7.77)	10.55 (2.73-11.43)	11.8 (4.96 - 13.1)	14.07 (3.52-15.24)	15.83 (4.10-16.71)
		Btu/h	18000 (9250-20000)	24000 (10990-26500)	36000 (9300-39000)	40200 (16900 - 44700)	48000 (12000-52000)	54000 (14000-57000)
Consumo	W	1450 (670-2027)	2300 (747-2930)	3900 (900-4250)	3700 (1158 - 4700)	5000 (900-5950)	5650 (1100-6650)	
	SEER	-	6.2	6.1	6.2	7	6.1	
Clasificación energética	Frio	A++						
Capacidad calefacción	Capacidad	kW	5.57 (2.42-6.30)	7.62 (2.72-8.29)	11.72 (2.78-12.78)	12.9 (3.8 - 14.9)	16.12 (4.10-17.00)	18.17 (4.40-19.64)
		Btu/h	19000 (8250-21500)	26000 (9280-28285)	40000 (9600-43600)	44000 (12900 - 50800)	55000 (14000-58000)	62000 (15000-67000)
	Consumo	W	1500 (540-1640)	2050 (650-2850)	3350 (800-3950)	3800 (1026 - 4800)	5100 (1000-6050)	6050 (1050-7100)
		SCOP	-	4.0		3.82		4.0
Clasificación energética	Calor	A+			A		A+	

CARACTERÍSTICAS

Unidad interior	Potencia sonora	dB(A)	57	55	64	66	67	
	Presión sonora	dB(A)	43.5/41/36.5/24	49/46/43/32	50/48.5/44/37	54/50/46	53/50/45/36	54/50.5/46.5/38
	Caudal de aire	m3/h	958/839/723	1192/1023/853	1955/1728/1504	2329/1930/1417	2100/1850/1600	2200/1950/1650
	Rango de temp. seleccionable	°C	16-30			17-30		16-30
Unidad exterior	Potencia sonora	dB(A)	65	66	68	72	73	
	Caudal de aire	m3/h	2100	3500	4000	3800	7500	
	Temp. de operación frío/calor	°C	-15-50 / -15-24					
	Compresor	GMCC						
Refrigerante	Tipo / Carga	R32/Kg	1,15		2,4	2,8	2,9	3
	Carga adicional > 5 m	g/m	12		24			

DIMENSIONES Y PESO

Unidad interior	Dim. netas (An×Al×Pr)	mm	1068x235x675			1650x235x675		
	Dim. brutas (An×Al×Pr)	mm	1145x318x755			1725x318x755		
	Peso neto	Kg	28/33.3	28/33.1	41.5/48	41.2	41.7/48.5	42.3/49.2
Unidad exterior	Dim. netas (An×Al×Pr)	mm	805x554x330	890x673x342	946x810x410		952x1333x415	
	Dim. brutas (An×Al×Pr)	mm	915x615x370	995x740x398	1090x885x500		1095x1480x495	
	Peso neto	Kg	32,5/35	44/47	80/85	73,9 / 78,9	104/118	107/121

CONEXIONES

Tubería frigorífica	Líquido - Gas	Pulg.	1/4" - 1/2"			3/8" - 5/8"			
	Longitud max.	m	30	50	75	65	75		
	Desnivel max.	m	20	25	30				
Conexiones eléctricas	Alimentación interior	mm	con la comunicación			2 x 2,5 + T		con la comunicación	
	Alimentación exterior	mm	2 x 2,5 + T		2 x 4 + T		4 x 4 + T		4 x 6 + T
	Interconexión (apantallado)	mm	3 x 1,5 + T			2 x 1,5		3 x 1,5 + T	